



## Technical Data Sheet

### 4M glossy nitro varnish

#### Characteristic properties

A glossy nitrocellulose transparent varnish that has a high covering ability and good adhesion on different types of transparent lining (nitro cellulose sealer).

Sealer Polyurethane - Sealer Polyester)

Viscosity : 4000 – 5000 c poise at 25 °C

Solid content : 47 ± 2%

Density : 0.90- 0.93 gm/cm<sup>3</sup>

Coverage : 6-8 m<sup>2</sup>/Kgm

Bending : good

the gloss : 90 - 100 on angle 60°

#### Materials for application

- glossy nitro varnish
- Thinner 5025

#### Suitable substrate and surface preparation

The surface must be well prepared and good sanding

The surface must be dry, smooth, free from dust and grease.

Suitable for painting wooden surfaces, windows, cupboards, boats and wooden kitchens.

As well as previously painted surfaces after removing all crusts and pimples.

#### Mixing ratio

**Dilute with Thinner 5025 to the right viscosity, then apply using a spray gun or brush**

#### Drying times at 20°C

	At 20°C
initial dryness	30 minute
Final dry	6-8 hours

Certified in ISO 9001, ISO 14001, ISO 45001

For additional information Kindly contact us at [info@4mcoatings.com](mailto:info@4mcoatings.com)

[www.4MCoatings.com](http://www.4MCoatings.com)



## Technical Data Sheet

### 4M glossy nitro varnish

#### Packaging

.900kgm – 3.250kgm

20kgm – 44kgm

#### color

clear

#### Expiry

1 years at 20°C

#### Material safety data

When using these products it is required to comply with the national regulations for health and safety

Certified in ISO 9001, ISO 14001, ISO 45001

For additional information Kindly contact us at [info@4mcoatings.com](mailto:info@4mcoatings.com)

[www.4MCoatings.com](http://www.4MCoatings.com)