

Technical Data Sheet

4M Sealer nitro extra

Characteristic properties

Clear nitrocellulose sealer has a high ability to cover and close the pores of wood, good adhesion to different types of wood, good sanding and good texture.

The product is suitable for interior use and can be sanded manually or mechanically.

Viscosity : 15000 - 20000 unit c poise at 25 °C

Solid content : 47 ± 2%

Density : 0.98 ± 0.02 gm/cm³

Coverage : 6-8 m²/Kg

Bending : good

Sanding : good

Materials for application

- Sealer Nitro extra
- Thinner 5025

Suitable substrate and surface preparation

The surface must be well prepared and sanded

The surface must be dry, smooth, free from dust and grease.

Suitable for painting wooden surfaces, windows, cupboards, boats and wooden kitchens.

As well as previously painted surfaces after removing all crusts and pimples.

Mixing ratio

Dilute with Thinner 5025 to the right viscosity, then apply using a spray gun or brush

Drying times at 20°C

	At 20°C
initial dryness	30minute
final dry	3-4 hours

Certified in ISO 9001, ISO 14001, ISO 45001

For additional information Kindly contact us at info@4mcoatings.com

www.4MCoatings.com



Technical Data Sheet

4M Sealer nitro extra

Packaging

0.900kg – 3.200kg – 25 kg

colour

clear

Expiry

1 years at 20°C

Material safety data

When using these products it is required to comply with the national regulations for health and safety

Certified in ISO 9001, ISO 14001, ISO 45001

For additional information Kindly contact us at info@4mcoatings.com

www.4MCoatings.com