



Technical Data Sheet

4M Hardener Polyurethane glossy colors Hardener

Characteristic properties

Polyurethane glossy colors Hardener gives high hardness, flexibility and chemical resistance to weathering, making it suitable for application as a stretch coating for any wood product.

It is suitable for both external and internal use. It is also water, scratch and abrasion resistant.

Materials for application

- Polyurethane glossy colors
- Polyurethane glossy colors Hardener
- Thinner 5025

Suitable substrate and surface preparation

Suitable for previously painted surfaces after removing all crusts and pimples

Suitable for painting wooden surfaces, and the surface must be dry, smooth, free from dust and grease

Mixing ratio

Polyurethane glossy colors	Polyurethane glossy colors Hardener	Thinner 5025
100	50	20-30

Pot life

5-6 hour at 20°C

Drying times

	20°C
initial dryness	90 minute
final dry	24 hours

Packaging

0.450 kgm

Certified in ISO 9001, ISO 14001, ISO 45001

For additional information Kindly contact us at info@4mcoatings.com

www.4MCoatings.com



Technical Data Sheet

4M Hardener Polyurethane glossy colors Hardener

Expiry

1 year at 20°C

color

clear

Material safety data

When using these products it is required to comply with the national regulations for health and safety

Certified in ISO 9001, ISO 14001, ISO 45001

For additional information Kindly contact us at info@4mcoatings.com

www.4MCoatings.com